

Datasheet

M.2 (S42) 3TE7 series

- M.2 SATA III solution for industrial field
- Exclusive L³ architecture
- DRAM-less, 100% data integrity
- Excellent random performance
- Supports TRIM/NCQ/SMART
- Built in iData Guard
- Compatible with M.2 2242-D2-B-M standard
- Designed with hardware LDPC ECC engine



Introduction

Innodisk M.2 (S42) 3TE7 SATA III Solid State Drive adopts latest SATA III NAND controller with Innodisk's exclusive L³ FW architecture which incorporates powerful LDPC technology into Innodisk signature 4K mapping L² FW architecture. 3TE7 series have outstanding high IOPS, better data integrity and extended lifespan through implementation of Die-Raid protection. Built-in thermal sensor and iData Guard also ensure data integrity and reliability of 3TE7 for industrial applications.

Innodisk M.2 (S42) 3TE7 is designed for industrial field and supports several advanced features including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides flexible customization service, making 3TE7 a perfect option for a variety of industrial applications.

M.2 (S42) 3TE7 series

Diagram

Contact us for more information
about the M.2 (S42) 3TE7.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)


5F., No. 237, Sec. 1, Datong Rd., Xizhi
Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2019 Innodisk Corporation.
All right reserved. Specifications are
subject to change without
prior notice.

20190425



Specifications

Interface	SATA III
Flash Type	3D TLC
P/E cycle	3,000
Capacity	32GB~1TB
Max. Channels	4
Sequential R/W (MB/sec, max.)	560/520
Max. Power Consumption	1.5W(470mA×3.3V)
Thermal Sensor	✓
External DRAM buffer	-
H/W Write Protect	Optional
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 42.0 X 3.5 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Operation Temp.	32GB	64GB	128GB	256GB	512GB	1TB
Standard Grade (0°C ~ +70°C)	DEM24-32GDK1*C1SL	DEM24-64GDK1*C1SL	DEM24-A28GDK1*C1DL	DEM24-B56DK1*C1DL	DEM24-C12DK1GCAQL	DEM24-01TDK1GCAQQ
Industrial Grade (-40°C ~ +85°C)	DEM24-32GDK1*W1SL	DEM24-64GDK1*W1SL	DEM24-A28GDK1*W1DL	DEM24-B56DK1*W1DL	DEM24-C12DK1GWAQL	DEM24-01TDK1GWAQQ

*. E: 64 Layers 3D TLC; G: 96 Layers 3D TLC

innodisk

www.innodisk.com

