

Datasheet

# U.2 SSD 4TG2-P series

- PCIe Gen. 4x4, NVMe 1.4
- Excellent data transfer speed
- Heat-spreading design
- LDPC ECC engine supported.
- End-to-end Data Path Protection
- High capacity & ultra-speed
- iCell feature



## Introduction

Innodisk U.2 SSD 4TG2-P is an NVM Express SSD designed as PCIe SFF-8639 module with PCIe interface and 3D TLC NAND Flash. U.2 SSD 4TG2-P supports PCIe Gen 4x4, and it is compliant with NVMe 1.4 providing excellent performance. With sophisticated error detection and correction (ECC) functions, the module can ensure full End-to-end Data Path Protection that secures the data transmission between host system and NAND Flash.

Innodisk U.2 SSD 4TG2-P provides ultra-speed and high IOPS and offers maximum capacity up to 4TB, making the SSD optimal for server and heavy data workload applications.

# U.2 SSD

## 4TG2-P series

Contact us for more information  
about the U.2 SSD 4TG2-P.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

### Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi  
Dist., New Taipei City 221, Taiwan  
Tel: +886-2-7703-3000  
Email: [sales@innodisk.com](mailto:sales@innodisk.com)


### Branch Offices:

USA  
[usasales@innodisk.com](mailto:usasales@innodisk.com)  
+1-510-770-9421  
Europe  
[eusales@innodisk.com](mailto:eusales@innodisk.com)  
+31-40-3045-400  
Japan  
[jpsales@innodisk.com](mailto:jpsales@innodisk.com)  
+81-3-6667-0161  
China  
[sales\\_cn@innodisk.com](mailto:sales_cn@innodisk.com)  
+86-755-21673689  
[www.innodisk.com](http://www.innodisk.com)

© 2022 Innodisk Corporation.  
All right reserved. Specifications are  
subject to change without  
prior notice.

20230628

### Diagram



Interface	PCIe Gen. 4 x4
Flash Type	3D TLC
P/E cycle	3,000
Capacity	512GB~4TB
Max. Channels	8
Sequential R/W (MB/sec, max.)	7100/6250
Max. Power Consumption	13.5W
Thermal Sensor	✓
External DRAM buffer	✓
H/W Write Protect	NA
iCell	NA
Dimension (WxLxH)	100.0 X 69.85 X 6.9 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Working Temperature: ST 0°C ~ +70°C, ; WT -40°C ~ +85°C Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

### Ordering Information

Operation Temp.	512GB	1TB	2TB	4TB
Standard Grade (0°C ~ +70°C)	DGEU2- C12DP1KCBFP	DGEU2- 01TDP1KCBFP	DGEU2- 02TDP1KCBFP	DGEU2- 04TDP1KCBFP
Industrial Grade (-40°C ~ +85°C)	DGEU2- C12DP1KWBEFP	DGEU2- 01TDP1KWBEFP	DGEU2- 02TDP1KWBEFP	DGEU2- 04TDP1KWBEFP

innodisk

[www.innodisk.com](http://www.innodisk.com)