


Datasheet

M.2 (P42) 4TE2 series

- PCIe Gen4 x4, NVMe SSD
- M.2 2242
- Standard/Wide-temperature
- Dynamic Thermal Management
- iPower Guard
- iData Guard



Introduction

Innodisk M.2 (P42) 4TE2 is a NVM Express DRAM-less SSD designed with PCIe interface and industrial 3D TLC NAND Flash. M.2 (P42) 4TE2 supports PCIe Gen4 x4 and it is compliant with NVMe 1.4 providing excellent top and also sustained performance. With sophisticated error detection and correction (ECC) functions, the module can provide full End-to-end Data Path Protection that secures the data transmission between the host system and NAND Flash.

M.2 (P42)

4TE2 series

Contact us for more information
about the M.2 (P42) 4TE2.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi
Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA

usales@innodisk.com

+1-510-770-9421

Europe

eusales@innodisk.com

+31-40-3045-400

Japan

jpsales@innodisk.com

+81-3-6667-0161

China

sales_cn@innodisk.com

+86-755-21673689

www.innodisk.com

© 2024 Innodisk Corporation.

All right reserved. Specifications are
subject to change without
prior notice.

202404

Diagram (ST)





Diagram (WT)



Contact us for more information about the M.2 (P42) 4TE2.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2024 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

202404

Specification

Interface	PCIe Gen4 x4
Flash Type	3D TLC
P/E cycle	3,000
Capacity	128GB~2TB
Max. Channels	4
Sequential R/W (MB/s, Max)	3,550/2,950
Max. Power Consumption (RMS)	5.0W
Thermal Sensor	√
External DRAM buffer	NA
Dimension (WxLxH)	ST with CU Foil: 22.0 X 42.0 X 4.1 mm WT with heatsink: 25.0 X 42.0 X 14.5 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	128GB	256GB	512GB	1TB	2TB
Standard Grade (0°C ~ +70°C)	DEM24-A28DF1KCADF	DEM24-B56DF1KCAQF	DEM24-C12DF1KCAQF	DEM24-01TDF1KCAQF	DEM24-02TDF1KCAQF
Industrial Grade (-40°C ~ +85°C)	DEM24-A28DF1KWADFH	DEM24-B56DF1KWAQFH	DEM24-C12DF1KWAQFH	DEM24-01TDF1KWAQFH	DEM24-02TDF1KWAQFH