

## M.2 (S80) 3IE6-P

### HIGHLIGHT FEATURES




- AES 256-bit encryption
- Excellent random performance
- End-to-end Data Path Protection
- iData Guard for abnormal power failure
- Supports TRIM / NCQ / S.M.A.R.T.
- Ultra iSLC technology
- Supports wide temperature from -40°C to 85°C

### SPECIFICATIONS

|                                 |                   |
|---------------------------------|-------------------|
| Model Name                      | M.2 (S80) 3IE6-P  |
| Flash Type                      | iSLC (3D TLC)     |
| Interface                       | SATA III 6.0 Gb/s |
| Form Factor                     | M.2 2280 B+M Key  |
| Capacity                        | 80GB ~ 160GB      |
| Sequential R / W (MB/sec, max.) | 490 / 480         |
| P/E Cycle                       | 100,000           |
| TBW (Max.)                      | 10,417            |
| Storage Temperature             | -40°C ~ 85°C      |
| Max. Power Consumption          | 2.6W              |
| Max. Channels                   | 4                 |
| External DRAM Buffer            | Y                 |
| H/W Write Protect               | Y (Optional)      |
| S.M.A.R.T.                      | Y                 |
| AES                             | Y (Optional)      |
| TCG Opal                        | Y (Optional)      |
| Dimension (W x L x H/mm)        | 22.0 x 80.0 x 3.5 |
| Vibration                       | 20G@[7 ~ 2000Hz]  |
| Shock                           | 1500G@0.5ms       |
| MTBF                            | >3 million hours  |
| Warranty                        | 5 Years           |

## DIAGRAM



## ORDER INFO.

| Operating Temperature | Standard Grade (0°C ~ 70°C) | Industrial Grade (-40°C ~ 85°C) |
|-----------------------|-----------------------------|---------------------------------|
| 80GB                  | DHM28-80GM71ECAQFS          | DHM28-80GM71EWAQFS              |
| 160GB                 | DHM28-A60M71ECAQFS          | DHM28-A60M71EWAQFS              |

**HQ (Taiwan)** T +886-2-7703-3000 / E sales@innodisk.com

**CN** T +86-755-2167-3689 / E sales\_cn@innodisk.com

**US** T +1-510-770-9421 / E [usasales@innodisk.com](mailto:usasales@innodisk.com)

**EU T +31-40-3045-400 / E eusales@innodisk.com**

**JP** T +81-3-6667-0161 / E [jp\\_sales@innodisk.com](mailto:jp_sales@innodisk.com)

innodisk