

M.2 (S80) 3SE2-P

HIGHLIGHT FEATURES



- SATA III solution for industrial field
- iSMART disk health monitoring
- Intelligent error recovery system
- Excellent data transfer speed
- Anti-vibration mechanical design
- Supports wide temperature from -40°C to 85°C

SPECIFICATIONS

Model Name	M.2 (S80) 3SE2-P
Flash Type	SLC
Interface	SATA III 6.0 Gb/s
Form Factor	M.2 2280 B+M Key
Capacity	8GB ~ 256GB
Sequential R / W (MB/sec, max.)	520 / 340
P/E Cycle	60,000
TBW (Max.)	6,000
Storage Temperature	-55°C ~ 95°C
Max. Power Consumption	2.3W
Max. Channels	4
External DRAM Buffer	Y
H/W Write Protect	N
S.M.A.R.T.	Y
AES	Y
TCG Opal	Y
Dimension (W x L x H/mm)	22.0 x 80.0 x 3.5
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	5 Years



Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
8GB	DEM28-08GD82SCADB	DEM28-08GD82SWADB
16GB	DEM28-16GD82SCADB	DEM28-16GD82SWADB
32GB	DEM28-32GD82SCADB	DEM28-32GD82SWADB
64GB	DEM28-64GD82SCADB	DEM28-64GD82SWADB
128GB	DEM28-A28D82SCADB	DEM28-A28D82SWADB
256GB	DEM28-B56D82SCADB	DEM28-B56D82SWADB

innodisk