

M.2 (S80) 3TG6-P

HIGHLIGHT FEATURES




- SATA III solution for industrial field
- High IOPS
- Excellent random performance
- End to end data path protection
- iData Guard for abnormal power failure
- PLP (iCell) technology for data protection

SPECIFICATIONS

Model Name	M.2 (S80) 3TG6-P
Flash Type	3D TLC
Interface	SATA III 6.0 Gb/s
Form Factor	M.2 2280 B+M key
Capacity	128GB ~ 2TB
Sequential R / W (MB/sec, max.)	560 / 490
P/E Cycle	3,000
TBW (Max.)	4,615
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	3.0W
Max. Channels	4
External DRAM Buffer	Y
H/W Write Protect	Y (Optional)
S.M.A.R.T.	Y
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	22.0 x 80.0 x 3.5
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	3 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
128GB	DGM28-A28M71%C*&FP	DGM28-A28M71%W*&FP
256GB	DGM28-B56M71%C*QFP	DGM28-B56M71%W*QFP
512GB	DGM28-C12M71%C*QFP	DGM28-C12M71%W*QFP
1TB	DGM28-01TM71%C*QFP	DGM28-01TM71%W*QFP
2TB	DGM28-02TM71KCBQFP	DGM28-02TM71KWBQFP

%. E : 64 layers 3D TLC / K : 112 layers 3D TLC

*. PCB version

&. D : 2 channels / Q : 4 channels

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

innodisk