

SATADOM-MH 3ME4

HIGHLIGHT FEATURES


- SATA III solution for industrial field
- Exclusive L³ architecture
- DRAM-less, 100% data integrity
- Excellent random performance
- Designed with hardware LDPC ECC engine
- Built-in Pin 8 power supply
- Supports wide temperature from -40°C to 85°C



SPECIFICATIONS

Model Name	SATADOM-MH 3ME4
Flash Type	MLC
Interface	SATA III 6.0 Gb/s
Form Factor	SATADOM-MH
Capacity	32GB ~ 256GB
Sequential R / W (MB/sec, max.)	530 / 210
P/E Cycle	3,000
TBW (Max.)	416
Storage Temperature	-55°C ~ 95°C
Max. Power Consumption	0.9W
Max. Channels	2
External DRAM Buffer	N
H/W Write Protect	Y
S.M.A.R.T.	Y
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	33.6 x 23.85 x 15.7
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	2 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
32GB	DESMH-32GM41BCADC*	DESMH-32GM41BWADC*
64GB	DESMH-64GM41BCADC*	DESMH-64GM41BWADC*
128GB	DESMH-A28M41BCADC*	DESMH-A28M41BWADC*
256GB	DESMH-B56M41BCADC*	DESMH-B56M41BWADC*

*PN end with A : Pin 8 + power cable / B : Pin 8 + Pin 7

