



SATADOM-SH 3TE7


HIGHLIGHT FEATURES

- SATA III solution for industrial field
- Exclusive L³ architecture
- DRAM-less, 100% data integrity
- Excellent random performance
- Designed with hardware LDPC ECC engine
- Built-in Pin 8 power supply
- Supports wide temperature from -40°C to 85°C

SPECIFICATIONS

Model Name	SATADOM-SH 3TE7
Flash Type	3D TLC
Interface	SATA III 6.0 Gb/s
Form Factor	SATADOM-SH
Capacity	64GB ~ 512GB
Sequential R / W (MB/sec, max.)	490 / 480
P/E Cycle	3,000
TBW (Max.)	1,000
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	1.5W
Max. Channels	2
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	Y
AES	Y (Optional)
TCG Opal	N
Dimension (W x L x H/mm)	33.05 x 18.0 x 15.2
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	3 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
64GB	DESSH-64GDK1KCASF*	DESSH-64GDK1KWASF*
128GB	DESSH-A28DK1KCADF*	DESSH-A28DK1KWADF*
256GB	DESSH-B56DK1KCADF*	DESSH-B56DK1KWADF*
512GB	DESSH-C12DK1KCADF*	DESSH-C12DK1KWADF*

*PN end with A : Pin 8 + power cable / B : Pin 8 + Pin 7

