



iCF 1ME2


HIGHLIGHT FEATURES

- CF 6.0 standard compatible
- Supporting PIO 0-6 / UDMA 0-6 in True-IDE mode
- Read disturb management
- Support Security Erase
- Support iPower Guard
- Support iData Guard

SPECIFICATIONS

Model Name	iCF 1ME2
Flash Type	MLC
Interface	PATA
Form Factor	CompactFlash (CF Card)
Capacity	8GB ~ 256GB
Sequential R / W (MB/sec, max.)	90 / 60
P/E Cycle	3,000
TBW (Max.)	750
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	0.9W
Max. Channels	2
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	Y
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	42.8 x 36.4 x 3.3
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	2 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
8GB	DECFC-08GYA2BC1SC	DECFC-08GYA2BW1SC
16GB	DECFC-16GYA2BC1DC	DECFC-16GYA2BW1DC
32GB	DECFC-32GYA2BC1DC	DECFC-32GYA2BW1DC
64GB	DECFC-64GYA2BC1DC	DECFC-64GYA2BW1DC
128GB	DECFC-A28YA2BC1DC	DECFC-A28YA2BW1DC
256GB	DECFC-B56YA2BC1DC	DECFC-B56YA2BW1DC

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

