USB Drive 3SE

HIGHLIGHT FEATURES

- High performance with USB 3.0 interface
- Low power consumption
- Wear-Leveling supported
- ECC engine coverage up to 60-bit / 1024 bytes
- Metal housing for robust usage
- 30µ golden finger for highly reliable data transfer quality

SPECIFICATIONS

Model Name	USB Drive 3SE
Flash Type	SLC
Interface	USB 3.0
Form Factor	USB Drive
Capacity	4GB ~ 32GB
Sequential R / W (MB/sec, max.)	100 / 85
P/E Cycle	60,000
TBW (Max.)	1,728
Storage Temperature	-40˚C ~ 85˚C
Max. Power Consumption	1W
Max. Channels	2
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	N
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	16.6 x 48.55 x 7.6
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	5 Years

DIAGRAM



Tolerence: ±0.20

ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
4GB	DEUA1-04GI61AC1SB	DEUA1-04GI61AW1SB
8GB	DEUA1-08GI61SCASB	DEUA1-08GI61SWASB
16GB	DEUA1-16GI61SCASB	DEUA1-16GI61SWASB
32GB	DEUA1-32GI61SCASB	DEUA1-32GI61SWASB

HQ (Taiwan) T +886-2-7703-8000 / E sales@innodisk.com
CN T +86-755-2167-3689 / E sales_cn@innodisk.com
EU T +31-40-8045-400 / E eusales@innodisk.com
US T +1-510-770-9801 / E usasales@innodisk.com
JP T +81-3-6667-0161 / E jp_sales@innodisk.com

© 2024 Innodisk Corporation. All right reserved. Specifications are subject to change without prior notice